













**STORE PRESSURE
15LB CO2 FIRE EXTINGUISHER
MODEL: CO15LB
STANDARD COMPLIED: DOT,ANSI/UL154**



Valve		024314001
Pressure Gauge		0242022
Cylinder		050100090
Hose Assembling		080100047
Bracket		070200007
		070100016
Seal		0714025
Safety Pin		020901003
Dip Tube		080402021
Hoop		070224004

**STORE PRESSURE
20LB CO2 FIRE EXTINGUISHER
MODEL: CO20LB
STANDARD COMPLIED: DOT,ANSI/UL154**



Valve		024314001
Pressure Gauge		0242022
Cylinder		050100091
Hose Assembling		080100047
Bracket		070202004
		070100022
Seal		0714025
Safety Pin		020901003
Dip Tube		080402022
Hoop		070224006

TECHNICAL SPECIFICATION

Model Number	CO15LB
Capacity(lb)	15
Cylinder Diameter(mm)	φ 175
Discharge Time(s)	15
Fire Rating	10-B:C
Extinguisher Weight	38lb(17.24kg)
Packing Size(L×W×H)(mm)	310×178×680
Operation Temperature (F)	- 22~120(-30℃~49℃)

* Transport Classification: Non-Flammable,Non Toxic Gass.
UN No.1044 Class 2.2

FEATURES:

Suitable for Class B and C Fires
Brass Material Valve With Stainless Stee Handle
Aluminum Cylinders
100% Leakage Detected
Production Under ISO9001 Quality System



TECHNICAL SPECIFICATION

Model Number	CO20LB
Capacity(lb)	20
Cylinder Diameter(mm)	φ 203
Discharge Time(s)	20
Fire Rating	10-B:C
Extinguisher Weight	49lb(22.20kg)
Packing Size(L×W×H)(mm)	330×205×690
Operation Temperature (F)	- 22~120(-30℃~49℃)

* Transport Classification: Non-Flammable,Non Toxic Gass.
UN No.1044 Class 2.2

FEATURES:

Suitable for Class B and C Fires
Brass Material Valve With Stainless Stee Handle
Aluminum Cylinders
100% Leakage Detected
Production Under ISO9001 Quality System



